



UTLY08-DF

UTLY24-SC

Spot/Flood Beams

Utility LED Bars

Benefits

- High-powered, heavy duty worklight bars available in a variety of lengths
- Ultimate mounting flexibility using a tilting pedestal mount or tilting surface mount
- Many lengths available with single or double row high-powered LEDs



Design Features

- Single and double row LED models
- Heavy-duty aluminum heatsink housing
- Polycarbonate Lens
- Spot and Flood models available as well as Spot/Flood combo models
- Lengths from 8" to 49"

Specifications

- Lengths of 8", 12", 14", 24", 25", 33", 36", 42", and 49".
- Depth is 3.3" for all bars
- Single row models are 2" in height
- Double row models are 3" in height
- 12/24 Volt
- IP67 Certified
- 3-year warranty

UTLY33-DC



UTLY08-SS

Prod No	Description	Lumens Raw/Effective
UTLY08-SF	LED BAR, 8", SINGLE, FLOOD, 12-56V	1100/1000
UTLY08-SS	LED BAR, 8", SINGLE, SPOT, 12-56V	1150/1100
UTLY08-DF	LED BAR, 8", DOUBLE, FLOOD, 12-56V	2150/1950
UTLY08-DS	LED BAR, 8", DOUBLE, SPOT, 12-56V	2450/2250
UTLY12-SC	LED BAR, 12", SINGLE, COMBO, 12-56V	2350/1900
UTLY14-SC	LED BAR, 14", SINGLE, COMBO, 12-56V	3350/2600
UTLY14-DC	LED BAR, 14", DOUBLE, COMBO, 12-56V	6700/4800
UTLY24-SC	LED BAR, 24", SINGLE, COMBO, 12-56V	5900/4400
UTLY25-DC	LED BAR, 25", DOUBLE, COMBO, 12-56V	12300/8800
UTLY33-DC	LED BAR, 33", DOUBLE, COMBO, 12-56V	16800/12000
UTLY36-SC	LED BAR, 36", SINGLE, COMBO, 12-56V	9250/6600
UTLY42-DC	LED BAR, 42", DOUBLE, COMBO, 12-56V	21300/15200
UTLY49-SC	LED BAR, 49", SINGLE, COMBO, 12-56V	12000/9000