

# SL Running Light

Extremely versatile solution brings added intersection safety



## FEATURES

- Distributes exceptional profile visibility to dangerous intersections
- Applications include: rocker panels, push bumpers, tailgates, headache racks, brow lights and more
- Lengths available in dual or split color functionality with the option of choosing three different colors in split mode
- Compact extruded aluminum housing is visually inconspicuous and weather resistant
- Orderable with vehicle-specific brackets and hardware for easy installation (sold separately)
- bluePRINT® compatible


## SPECIFICATIONS

Input Voltage Range	10-30 Vdc
Amperage Draw	0.58 Amp @ 12.8 Vdc
Operating Temperature	-40°C to +65°C
LED Count	12 LEDs per module
Flash Patterns	69
Dimensions	15", 50", 61.4", or 72.8" L x 1.09" H x .75" D
Mount Types	Bracket mount (sold separately)



## PART NUMBERS

<b>Part Number</b> ESLRL1511D ESLRL1511E ESLRL1511F ESLRL1511J ESLRL15118	<b>15" (1 module)</b> Dual Color, Red/White Dual Color, Blue/White Dual Color, Amber/White Dual Color, Red/Blue Dual/Split Color, Red/Blue/White	<b>Part Number</b> ESLRL6115D ESLRL6115E ESLRL6115F ESLRL6115J ESLRL61158	<b>61.4" (5 modules)</b> Dual Color, Red/White Dual Color, Blue/White Dual Color, Amber/White Dual Color, Red/Blue Dual/Split Color, Red/Blue/White
<b>Part Number</b> ESLRL5014D ESLRL5014E ESLRL5014F ESLRL5014J ESLRL50148	<b>50" (4 modules)</b> Dual Color, Red/White Dual Color, Blue/White Dual Color, Amber/White Dual Color, Red/Blue Dual/Split Color, Red/Blue/White	<b>Part Number</b> ESLRL7316D ESLRL7316E ESLRL7316F ESLRL7316J ESLRL73168	<b>72.8" (6 modules)</b> Dual Color, Red/White Dual Color, Blue/White Dual Color, Amber/White Dual Color, Red/Blue Dual/Split Color, Red/Blue/White



Scan to order  
or learn more

## CONTACT

Toll free 800.338.7337  
Direct 616.896.7100  
[soundoffsignal.com](http://soundoffsignal.com)

PO Box 206  
Hudsonville, MI 49426  
[customerservice@soundoffsignal.com](mailto:customerservice@soundoffsignal.com)

V0424