

# obSERVE+ Dome Light, 3"

Powerful interior lighting in a sleek design



White LED



Blue LED



Red LED



White LED w/ Flush Mount Grommet

## FEATURES

- Offers a low amp draw, superior efficiency and hours of long-lasting reliability
- Low profile, surface mount design allows for multiple mounting options and easy installation
- Dual color with individual control
- High performing, standard sized interior compartment light
- Low Power/Dim modes
- Soft on/off

## SPECIFICATIONS

<b>Input Voltage Range</b>	10-32 Vdc
<b>Standby Current</b>	<0.125mA
<b>Max Current</b>	0.45 amps
<b>Max Power</b>	5.4 watts
<b>Operating Temperature</b>	-40° C to +65° C (-40° F to +149° F)
<b>Electrical Protection</b>	Reverse polarity, transient protection
<b>LED Color Capabilities</b>	Single and dual color
<b>LED Count</b>	Single - 6 LEDs, Dual - 3 white + 3 colored LEDs
<b>Optic Type</b>	Flood pattern
<b>Raw Lumens</b>	Single - 390 lm (white), Dual - 350 lm (white), 100 lm (blue), 110 lm (red)
<b>Mount Types</b>	Surface mount with adhesive and screw options, Flush mount grommet option ( <i>sold separately</i> )
<b>Dimensions</b>	3.2" Dia x 0.4" D (82mm Dia x 10mm D)
<b>Wire Length</b>	8" (200mm)
<b>Materials</b>	Polycarbonate lens, aluminum heatsink, ABS plastic bezel
<b>Certifications</b>	ECE R10, CISPR25 Class 3
<b>IP Rating</b>	IPx8

## PART NUMBERS

Single Color, White — ○  
Flush Mount Grommet

**EBSDL0001-W**  
**PBSDLGM01**

Dual Color, Red/White — ●○  
Dual Color, Blue/White — ●○

**EBSDL0002-D**  
**EBSDL0002-E**



Scan to order  
or learn more

Refer to [soundoffsignal.com](http://soundoffsignal.com) for standard part numbers and complete offerings.

## CONTACT

Toll free 800.338.7337  
Direct 616.896.7100  
[soundoffsignal.com](http://soundoffsignal.com)

PO Box 206  
Hudsonville, MI 49426  
[customerservice@soundoffsignal.com](mailto:customerservice@soundoffsignal.com)

**V0623**