



Introducing the nFORCE NXT lightbar.

This is the next generation of the industry's best lightbar, nFORCE. We've bumped up brightness, lowered the amps, and made it harder working than ever before. You deserve our best.

15%

INCREASE IN LED OUTPUT

20%

REDUCTION IN POWER
CONSUMPTION

Features

- ✓ Now available with tinted lenses
- ✓ Built-in photo cell
- ✓ 3-wire install
- ✓ Plugs directly into 500 Series Siren without the need for a BOB

Symmetrical
Endcaps

Sleek
Look

3-Wire
Circuitry

Easier
Install

Multi-color
Alleys

You asked
for it!


Lower profile

by
10%

LAUNCHING
Summer 2021

[soundoffsignal.com/product/
nforce-nxt](https://soundoffsignal.com/product/nforce-nxt)

Contact your Sales Rep to order.


nFORCE[®] next Exterior Full Size Lightbar
 NEXUS TECHNOLOGY


ENNLB

● ● ● ● ○ To order configured products, contact your sales representative or customer service department.

Modules

- Modules can be configured as single, dual or tricolor for maximum functionality
- Inboard modules are offered in single color 6 LEDs, dual color 12 LEDs or tricolor 18 LEDs
- Corner modules are offered in single color 12 LEDs, dual color 24 LEDs or tricolor 36 LEDs
- Alley modules are offered in single color 3 LEDs, dual color 6 LEDs or tricolor 9 LEDs

Specs

INPUT VOLTAGE RANGE 10-32 Vdc

NUMBER OF LEDS AND MAXIMUM CURRENT DRAW @ 12.8 VDC

Inboard Warning Modules 6 LED Single Color: <1.0 Amp; 12 LED Dual Color: <1.0 Amp or 18 LED Tricolor < 1.0 Amp
Corner Modules 12 LED Single Color: <2.0 Amp; 24 LED Dual Color: <2.0 Amp or 36 LED Tricolor: <2.0 Amp
Takedown 6 LED Single Color: =1.0 Amp
Alley 3 LED Single Color: <0.6 Amp; 6 LED Dual Color: <0.6 Amp; 9 LED Tricolor < 0.6 Amp

NUMBER OF LEDS AND MAXIMUM WATTAGE @ 12.8 VDC

Inboard Warning Modules 6 LED Single Color: <6.4 Watts; 12 LED Dual Color: <6.4 Watts or 18 LED Tricolor: <6.4 Watts
Corner Modules 12 LED Single Color: <12.8 Watts; 24 LED Dual Color: <12.8 Watts or 30 LED Tricolor: <12.8 Watts
Takedown 6 LED: <12.8 Watts
Alley 3 LED: <6.4 Watts

FLASH PATTERNS Warning 66 Takedown/Alley 25 Arrow L/C/R 11

OPERATING TEMPERATURE -40° C to +65° C / -40° F to +149° F

DIMENSIONS

Lengths 2 Module: 24" (61 cm); 4 Module: 36" (91 cm); 5 Module: 42" (107 cm); 6 Module: 48" (122 cm); 7 Module: 54" (137 cm);
 8 Module: 60" (152 cm) or 10 Module: 72" (183 cm)

Height Lightbar 2.34" (5.8 cm)

Depth Lightbar 12" (31 cm)

MOUNTS

Standard hook kit mount with angle adjustment wedge
 Headache rack mount

CERTIFICATIONS

SAE J845/J595 Class 1 (Red, Blue, Amber, White, Green)
 CA Title 13, Table 1, Class B (Red, Blue, Amber)
 NFPA 1901 for all zones (Red, Blue, Amber, White)
 ECE R65 Category T, Class 2 (Red, Blue, Amber), ECE R10.06

WARRANTY

Five-year

CONTACT US



www.soundoffsignal.com



800.338.7337 / 616.896.7100



Fax 616.896.1226 / Order fax 616.896.1286