## CD5051VDL2 SERIES



Code 3's low-profile, Matrix® compatible CD5051VDL2 deck, dash and visor light delivers discreet warning wherever an interior light is needed in a patrol unit, undercover unit or any other vehicle in the fleet. Permanently or temporarily mount the emergency warning light with included brackets using suction cups, tape or screws. The dual-color LED light heads are available in combinations of white and amber, red or blue colors, which are capable of producing 67 flash patterns including steady-burn. The cigarette plug adapter also includes a simple two-button controller. The removable shroud prevents unwanted flash back from the windshield.



VOLTS   AMPS	12-24V   1.7A
DIMS	0.8" H x 11.4" W x 1.6" D   20mm H x 290mm W x 40mm D (no shrou 1.1" H x 12.1" W x 3.0" D   28mm H x 308mm W x 76mm D (shroud)
WATTS	21.1
FLASH PATTERNS	67
CERTS	CLASS I, CA T13, RCM, R65, R10, RoHS
DETAILS	Contains 2 CD5051 dual-color lightheads in a compact unit  Sleek design for low-profile applications  Removable visor hood for versatile use on deck, dash or windows  Multiple brackets included for permanent mount (screws or tape) or removable (suction cups)  Cigarette plug adapter and controller with flash pattern selector  Matrix Compatible  Temperature range: -40°F to 149°F (-40°C to 65°C)

MODEL	ТҮРЕ	ILLUMINATION COLORS
CD5051VDL2-AW	Dual-color heads / visor, deck,dash	AW
CD5051VDL2-BW	Dual-color heads / visor, deck,dash	BW
CD5051VDL2-RW	Dual-color heads / visor, deck,dash	RW
CD5051VDL2-RWBW	Dual-color heads / visor, deck,dash	RWBW

## No Shroud 0.8[20] 1.7[44] 12.8[326] FRONT VIEW, WITHOUT SHROUD 2X Ø 0.20[5] MOUNTING HOLES 1.9[48] 1.6 40 12.20[310] TOP VIEW, WITHOUT SHROUD

## With shroud

